

# Sea Me by FusionBeads.com



Approximate finished length: 7 inches

## **Beads and other products needed for one bracelet:**

- 7 - 5x7mm Olivine Fire Polished Rondelles (FP1314)
- 7 - 5x7mm Teal Fire Polished Rondelles (FP1316)
- 7 - 5x7mm Turquoise Fire Polished Rondelles (FP1317)
- 4 crystals - SS9 Olivine Swarovski Crystal Flat Back Rhinestones (FT1143)
- 22 - 5mm Rhodium Plated Nugget Heishis (SP0300)
- 1 - 21.8x16.5mm Antique Silver Plated Leaf Toggle Clasp (SP2326)
- 2 - 2x2mm Sterling Silver Crimp Beads (SS4047)
- 2 - 3.4mm Sterling Silver Crimp Bead Covers (SS2103)
- 1 foot - Clear Soft Flex Beading Wire .014 Diameter (SM0310)

## **Tools needed to complete the bracelet:**

- Wire cutters
- Crimping pliers (TL0500)
- Jewel Setter or tweezers
- Hypo Tube Cement

## **Beading Techniques needed to complete the bracelet:**

- Crimping
- Crimp Bead Covers
- Gluing Flat Back Rhinestones into a Charm

*For step-by-step photos and instructions on these and other techniques, visit [FusionBeads.com](http://FusionBeads.com) and select Beading Techniques from the top navigation bar.*

## **Instructions to complete "Sea Me" bracelet:**

### **Step 1**

Place a dot of Hypo Tube Cement into the open divot on the antique silver plated leaf toggle clasp. Using a Jewel Setter, place one Olivine flat back rhinestone onto the glue. Use tweezers or a fingernail to release the rhinestone from the Jewel Setter and gently press the rhinestone into the glue (see Gluing Flat Back Rhinestones Technique).

### **Step 2**

When the first rhinestone has set, repeat Step 1 three times, gluing the three remaining Olivine flat backs into the three divots on the toggle clasp.

### **Step 3**

When all four rhinestones have set, place one crimp bead and the loop on one side of the toggle clasp onto a 1-foot length of beading wire. Pass the wire back through the crimp bead, and crimp the crimp bead (see Crimping Technique).

### **Step 4**

Cover the crimp bead with a crimp cover (see Crimp Bead Covers Technique), and trim excess wire with wire cutters.

### **Step 5**

String these beads in the following sequence onto the beading wire:

1 - rhodium plated nugget heishi

\*\*1 - olivine fire polished rondelle

1 - heishi

1 - teal rondelle

1 - heishi

1 - turquoise rondelle

1 - heishi

Repeat from the \*\* six times

1 - crimp bead

The loop on the other side of the toggle clasp

### **Step 6**

Pass the wire back through the crimp bead, crimp the crimp bead, cover with a crimp cover, and trim excess wire with wire cutters.

**For more Inspiration jewelry ideas and to meet all your beading needs, visit [FusionBeads.com](http://FusionBeads.com)!**